

Twofold Warning System Multi-Light 340 LED Flash L9M

- Energy-efficient LED technology
- Automatic day/night adaptation, switchable to solar switch
- Consisting of one master lamp and one slave lamp, cable length between the lamps 5 m
- Master lamp with 5 m connecting cable with battery clips
- Bracket for tubes up to 82 mm (optional)



Light colour yellow	Eff. light intensity day 4900 cd	Av. power consumpt. day 0.1 A	Operating voltage 12/24 V
Blink-/flash rate 60 fl./Min.	Light source 4 LED	Weight 5.4 kg/set	

Twofold Warning System Multi-Light 340 LED Flash L9M

Order number

Twofold Warning Light System Multi-Light 340 LED Flash L9M 690/1F NiBus 12/24V, with bracket, 5 m connecting cable with battery clips on master lamp

122312-201

Accessories and Spare parts

Order number

Box for rechargeable batteries 12 V up to 230 Ah, lockable

190230-1

Operating time with a battery pack

With rechargeable battery 12 V, 100 Ah


750 hrs

With rechargeable battery 12 V, 180 Ah

1500 hrs



Twof. W. S. Multi-Light 340 LED Flash L9M



Twofold Warning S. with bracket



Box for rechargeable batteries



Further information
NIS-00796
Entry on nissen-germany.com

Verification number:
V4-70-2011

