

Star-Flash LED 627 FEUERWEHR

- Stabile Synchronisation über Infrarot
- Ketten mit beliebiger Länge und Leuchtenanzahl möglich
- Energieeffiziente Konstruktion mit nur einer LED
- Automatisches Umschalten auf Batteriebetrieb bei entladenem Akku
- Große Standfestigkeit durch vier ausdrehbare Standfüße
- Schriftzug FEUERWEHR retroreflektierend



Light colour gelb	Eff. light intensity day 500 cd / 250 cd	Eff. light intensity night 60 Bl./Min.	Eff. light intensity day / night 500 cd / 250 cd
Blink-/flash rate 1 LED bzw. 2 LED	Light source 1 LED bzw. 2 LED	Dimensions (LxWxH) 370 x 205 x 95 mm	Weight ca. 1,8 kg

Star-Flash LED 627 FEUERWEHR

Order number

Star-Flash LED Type 627 B guide light lamp, one-sided amber (According to German Standards), for battery operation , without battery	129091-013-01
Star-Flash LED Type 627 B guide light lamp, two-sided amber for battery operation , without battery	129091-013-02
Each consisting of: Housing colour red, bottom and lock black, retroreflecting text "FIRE BRIGADE", without transport and charging cradle	

Accessories and Spare parts

Order number

Adapter for using the Nitra, Euro-Nitra, Star-Flash and City Flash on traffic cones	081736-1
AC/DC converter 110-240V, 12V, 5A, for indoor use only, with cigarette lighter socket (for Star-Flash LED 620/627 A)	070098-1
Lithium-Ferro rechargeable battery pack 6,5 V, 1500 mAh for Star Flash 620A/627A	056056-2
Transport and charging cradle 12/24 V for Star-Flash LED Type 620/627, 4-fold, with 2 m supply cable and 2-pole vehicle plug	129090-004-01
Transport and charging cradle 12/24 V for Star-Flash LED Type 620/627, single, with 2 m supply cable and 2-pole vehicle plug	129090-001-01
Transport cradle 12/24 V for Star-Flash LED Type 620/627, single, without supply cable	129090-001-00

Operating time with a battery pack

With integrated Lithium-Ferro rechargeable battery pack	40 Std.
With battery Premium 800	180 Std.



In Transport- und Ladeschale



Führungslicht



4-fach Transport- und Ladeschale



Adapter für Leitkegel



Further information
NIS-01108
Entry on nissen-germany.com

Verification number:
V4-25-2012