

Star-Flash LED 620

- Only one LED, therefore low current consumption and long operating times
- Automatic day/night adaptation
- Optionally with transport- and charging cradle, freely expandable
- Basic steady light for increased visibility at darkness
- With four swivel-out support feet, therefore high stability
- Space-saving storage due to slim design



Light colour
amber



Eff. light intensity day
500 cd / 250 cd



Eff. light intensity day / night
500 cd / 250 cd



Blink-/flash rate
60 fl./min.



Light source
1 resp. 2 LED



Dimensions (LxWxH)
370 x 205 x 95 mm



Weight
ca. 1.8 kg


Star-Flash LED 620

Order number

Star-Flash LED 620 A, one-sided amber housing colour yellow, bottom and lock black, with integrated lithium ferro battery pack	129092-001-01
Star-Flash LED 620 A, two-sided amber housing colour yellow, bottom and lock black with integrated lithium ferro battery pack	129092-001-02
Star-Flash LED 620 B, one-sided amber housing colour yellow, bottom and lock black for battery operation , without battery	129092-011-01
Star-Flash LED 620 B, two-sided amber housing colour yellow, bottom and lock black for battery operation , without battery	129092-011-02



In transport and charging cradle



1-fold transport and charging cradle

Accessories and Spare parts

Order number

Transport cradle 12/24V for Star-Flash LED Type 620/627, single, without supply cable	129090-001-00
Transport and charging cradle 12/24V for Star-Flash LED Type 620/627, single, with 2 m supply cable and 2-pole vehicle plug	129090-001-01
Transport and charging cradle 12/24V for Star-Flash LED Type 620/627, 4-fold, with 2 m supply cable and 2-pole vehicle plug	129090-004-01
Lithium-Ferro rechargeable battery pack 6,5 V, 1500 mAh for Star Flash 620A/627A	056056-2
Adapter for using the Nitra, Euro-Nitra, Star-Flash and City Flash on traffic cones	081736-1
AC/DC converter 110-240V, 12V, 5A, for indoor use only, with cigarette lighter socket (for Star-Flash LED 620/627 A)	070098-1



4-fold transport and charging cradle



Adapter for traffic cone

Operating time with a battery pack

With integrated Lithium-Ferro rechargeable battery pack	40 hrs
With battery Premium 800	180 hrs



Further information
NIS-01201
Entry on nissen-germany.com

Verification number:
V3-34-2014