Star-Flash LED 620

- Only one LED, therefore low current consumption and long operating times
- Automatic day/night adaptation
- Optionally with transport- and charging cradle, freely expandable
- Basic steady light for increased visibility at darkness
- With four swivel-out support feet, therefore high stability
- Space-saving storage due to slim design







Light colour amber



Eff. light intensity day 500 cd / 250 cd



Eff. light intensity day / night 500 cd / 250 cd

200 mm



Blink-/flash rate 60 fl./min.

nissen

amp class

L8L

L8M

ding to ENT?

St approved



Light source 1 resp. 2 LED



Dimensions (LxWxH) 370 x 205 x 95 mm

Order number

129092-011-02



Weight ca. 1.8 kg

Star-Flash LED 620

Star-Flash LED 620 A, one-sided amber housing colour yellow,
bottom and lock black, with integrated lithium ferro battery pack

Star-Flash LED 620 A, two-sided amber
housing colour yellow, bottom and lock black
with integrated lithium ferro battery pack

Star-Flash LED 620 B, one-sided amber
housing colour yellow, bottom and lock black
for hotton careatter, without hottors

for battery operation, without battery Star-Flash LED 620 B, two-sided amber housing colour yellow, bottom and lock black

for battery operation, without battery



In transport and charging cradle



1-fold transport and charging cradle

Accessories and Spare parts Order number

AC/DC converter 110-240V, 12V, 5A, for indoor use only, with cigarette lighter socket (for Star-Flash LED 620/627 A)	070098-1
Adapter for using the Nitra, Euro-Nitra, Star-Flash and City Flash on traffic cones	081736-1
Lithium-Ferro rechargeable battery pack 6,5 V, 1500 mAh for Star Flash 620A/627A	056056-2
Transport and charging cradle 12/24 V for Star-Flash LED Type 620/627, 4-fold, with 2 m supply cable and 2-pole vehicle plug	129090-004-01
Transport and charging cradle 12/24 V for Star-Flash LED Type 620/627, single, with 2 m supply cable and 2-pole vehicle plug	129090-001-01
Transport cradle 12/24 V for Star-Flash LED Type 620/627, single, without supply cable	129090-001-00

Operating time with a battery pack

With integrated Lithium–Ferro rechargeable battery pack	40 hrs
With battery Premium 800	180 hrs



4-fold transport and charging cradle



Adapter for traffic cone

Verification number: V3-34-2014