

Warning Trailer

A41



CHASSIS AND BODY

- Modular design, separately bolted, galvanized and interchangeable
- Galvanized, height-adjustable drawbar (Al-Ko), with overrun brake, holding brake and parallel adjustment
- DIN towing eye with a changeable spherical head coupling
- Loading ramp surfaced with aluminium chequered plate
- Loading area of 15 mm 7 layered laminated plywood sheets with sealed edges
- Side panels of 15 mm 7 layered laminated plywood covered with aluminium sheet profil at the top
- Height-adjustable semi-automatic support wheel
- Robust plastic fenders
- 2 battery boxes of steel with aluminium chequered plate cover (950 x 630 x 300 mm)
- Support frame for the drawbar of a loaded warning board
- Manual cable winch with a hook and 10 m of cable
- Rubber spring axle with a tandem brake design with automatic brake adjustment
- 6 lashing points (straps) with 500 daN
- 2 fully adjustable support legs
- Loading aid incl. hopper opening

WARNING BOARD

- Warning board in compliance with RSA 21 and ZTV-SA, 3600 x 2200 mm
- Chevron patterned plates and directional arrow with microprismatic retro-reflective foil, type RA2
- Light arrow system with two LED warning lamps (WL5) and 25 separately monitored LED warning lamps (WL6)
- Directional arrow with motor revolution, mechanical emergency and automatic light arrow adjustment
- Motorized lifting/lowering of the top board with mechanical emergency adjustment and emergency-off switch
- Combined manual radio-cable control for activating all functions via touchscreen and one-touch keys

ELECTRICAL SYSTEM

- Rechargeable battery 12 V up to 80 hours daytime operation (further energy packages on request)
- Trailer lighting 12 V and/or 24 V
- Feed socket 230 V
- Battery charger
- Battery guard for protection of electronics
- LP 8000 approved according to EMC directive

ACCESSORIES AND OPTIONS

- Repeater of the vehicle lighting
- Cargo securing set and central crank supports
- Acoustic signalling device for manual control
- Control and monitoring system
- Firm rear frame
- Winch, set for lashing straps, traffic cone holder, spare wheel with holder, holder for warning threshold



Technical data

Total weight	2000 - 2500 kg
Empty weight depending on model	1100 - 1300 kg
Total length	6800 - 7200 mm
Total width	2400 mm
Track width	2200 mm
Loading area (LxW)	3100 x 1820 mm
Side boards (H)	300 mm
Clearance width	1830 mm
Clearance height	1878 mm
1050 - 1350 kg	900 - 1400 kg

Warning Trailer Type A41

Order number

Warning Trailer Type A41 in modular construction

129717-041



Further information
NIS-01220
Entry on nissen-germany.com