

CHASSIS AND BODY

- Chassis and body of hot-galvanized steel
- Hot-galvanized, height-adjustable drawbar with holding brake
- DIN towing eye and spherical head coupling changeable
- Height-adjustable support wheel
- 4 fully adjustable support legs
- Battery box of acid-proof plastic (1660 x 450 x 320 mm)
- Plastic fenders
- Warning marking in accordance with DIN 30710 at the rear and additional warning markings at the sides
- Handle for one-handed opening/closing of battery box

ADVANCE WARNING BOARD

- 2 LED advance warning lamps inspected in compliance with TL warning lamps WL 7
- 2 LED variable message signs with an automatic and manual brightness adjustment for the static and dynamic representation of texts, symbols and road signs

Upper LED variable traffic sign

Housing size: 970 x 970 mm
LED display surface: 840 x 840 mm
Pixels: 42 x 42
Grid dimension: 20 mm
LED/m²: 2500

Lower variable traffic sign

Housing size: 1390 x 1810 mm
LED display surface: 1260 x 1680 mm
Pixels: 63 x 84
Grid dimension: 20 mm

- LED/m²: 2500
 Separately programmable text line
- Libraries on a separate memory module
- Motorized lifting and lowering of the top board with mechanical emergency adjustment and freely accessible emergency-off switch
- Electromotive locking in lowered state
- Combined manual radio-cable remote control for operating all functions via touchscreen and one-touch keys
- Free programming software

ELECTRICAL SYSTEM

- Rechargeable battery, 24 V with up to 50 hours daytime operation (further energy packages on request)
- Trailer lighting optionally 12 V and/or 24 V
- Feed socket 230 V
- Battery guard for protection of electronics
- Battery charger

ACCESSORIES AND OPTIONS

- Central crank supports
- Control and monitoring system
- · Operating hours counter
- · Interface package



Side view



Lowered

Technical data

Total weight	750 - 1000 kg
Empty weight depending on model	620 - 720 kg
Total length	4450 - 5800 mm
Total width	1810 mm
Track width	1600 mm
Max. load capacity	30 - 380 kg
Height lifted	3596 mm
Height lowered	1475 mm

VarioSign LED Trailer STANDARD

Order number

Advance Warning Trailer VarioSign STANDARD with LED variable message signs total weight 750 – 1000 kg, with parking brake

129265-011



Further informationNIS-01787
Entry on nissen-germany.com