

# Twofold Warning System Zyklus 220 LED L8H

- Energy-efficient design with only one LED
- Automatic day/night adaptation, switchable to solar switch
- 5 m connecting cable with battery clips per system
- Consisting of one master lamp and one slave lamp, cable length between the lamps ca. 3 m
- Approved according to EMC directive
- Bracket for tubes up to 82 mm (optional)



**Light colour**  
amber



**Eff. light intensity**  
1500 cd



**Av. power consumpt. day**  
0.28 A



**Operating voltage**  
12/24 V



**Blink-/flash rate**  
60 fl./min.



**Light source**  
1 LED



**Weight**  
1.2 kg/set



**Av. power consu2**  
12/24 V

## Twofold Warning System Zyklus 220 LED L8H

### Order number

Twofold Warning Light System Zyklus 220 LED L8H, 671/1 NiBus, 12/24 V, with 5 m connecting cable with battery clips on master lamp

122222-1

## Accessories and Spare parts

### Order number

Box for rechargeable batteries 12 V up to 230 Ah, lockable  
Bracket for tubes up to 82 mm

190230-1  
365522-12

## Operating time with a battery pack

With rechargeable battery 12 V, 100 Ah  
With rechargeable battery 12 V, 180 Ah  
With rechargeable battery 12 V, 230 Ah

440 hrs  
800 hrs  
1000 hrs



twof. Warning System Zyklus 220 LED L8H



Twofold Warning System with bracket



Box for rechargeable batteries



Further information  
NIS-01411  
Entry on [nissen-germany.com](http://nissen-germany.com)

Verification number:  
V3-24-2013

