

Twofold Warning System Zyklus 220 LED L8H

- Energy-efficient design with only one LED
- Automatic day/night adaptation, switchable to solar switch
- 5 m connecting cable with battery clips per system
- Consisting of one master lamp and one slave lamp, cable length between the lamps ca. 3 m
- Approved according to EMC directive
- Bracket for tubes up to 82 mm (optional)



Light colour amber	Eff. light intensity 1500 cd	Av. power consumpt. day 0.28 A	Operating voltage 12/24 V
Blink-/flash rate 60 fl./min.	Light source 1 LED	Weight 1.2 kg/set	Av. power consu2 12/24 V

Twofold Warning System Zyklus 220 LED L8H

Order number

Twofold Warning Light System Zyklus 220 LED L8H, 671/1 NiBus, 12/24 V, with 5 m connecting cable with battery clips on master lamp 122222-1

Accessories and Spare parts

Order number

Bracket for tubes up to 82 mm 365522-12
Box for rechargeable batteries 12 V up to 230 Ah, lockable 190230-1

Operating time with a battery pack

With rechargeable battery 12 V, 100 Ah 440 hrs
With rechargeable battery 12 V, 180 Ah 800 hrs
With rechargeable battery 12 V, 230 Ah 1000 hrs



twof. Warning System Zyklus 220 LED L8H



Twofold Warning System with bracket



Box for rechargeable batteries



Further information
NIS-01411
Entry on nissen-germany.com

Verification number:
V3-24-2013

