

BakoLight LED

- Easy mounting on beacon systems
- Easy attachment to barriers and to tubes with the optional bracket
- Automatic solar switch and stand-by indicator
- Only one battery integrated, therefore no cable connection



Light colour
amber or red



Eff. light intensity
amber one-sided 20 cd /
two-sided 12 cd



Eff. light intensity
red one-sided 23 cd



Blink-/flash rate
60 - 70 fl./min.



Light source
1 resp. 2 LED




Dimensions (LxWxH)
267 x 105 x 275 mm



Weight
0,8 kg



BakoLight LED on a Safety Beacon



BakoLight LED on a Safety Barrier



Key



BakoLight with bracket

BakoLight LED

Order number

BakoLight LED, flashing/steady light, one-sided amber, with bracket	111241-51
BakoLight LED, flashing/steady light, one-sided red, with bracket	111241-53
BakoLight LED, flashing/steady light, two-sided amber, with bracket	111242-51
BakoLight LED, flashing/steady light, one-sided amber, without bracket	111241-1
BakoLight LED, flashing/steady light, two-sided amber, without bracket	111242-1
BakoLight LED, flashing/steady light, one-sided red, without bracket	111241-3

Accessories and Spare parts

Order number

Bracket for mounting the MonoLight and BakoLight	070877
Key	070090-3
Pin	010393

Operating time with a battery pack

With battery Premium 800	one-sided steady light 250 hrs flashing light 750 hrs
	two-sided steady light 300 hrs flashing light 900 hrs
With battery Konstant 25	one-sided steady light 500 hrs flashing light 1500 hrs
	two-sided steady light 1000 hrs flashing light 3000 hrs



Packaging Unit
10 pcs in one carton / 200 pcs on one pallet
also available in other quantities



Further information
NIS-00741
Entry on nissen-germany.com

Verification number:
V4-01-2004 V4-02-2004 V4-47-2004