


BakoLight LED


- Easy mounting on beacon systems
- Easy attachment to barriers and to tubes with the optional bracket
- Automatic solar switch and stand-by indicator
- Only one battery integrated, therefore no cable connection



Light colour amber or red	Eff. light intensity amber one-sided 20 cd / two-sided 12 cd	Eff. light intensity red one-sided 23 cd	Blink-/flash rate 60 - 70 fl./min.
Light source 1 resp. 2 LED	Dimensions (LxWxH) 267 x 105 x 275 mm	Weight 0,8 kg	



BakoLight LED on a Safety Beacon



BakoLight LED on a Safety Barrier



Key



BakoLight with bracket

BakoLight LED

Order number

BakoLight LED, flashing/steady light, one-sided red, with bracket	111241-53
BakoLight LED, flashing/steady light, two-sided amber, with bracket	111242-51
BakoLight LED, flashing/steady light, one-sided amber, without bracket	111241-1
BakoLight LED, flashing/steady light, two-sided amber, without bracket	111242-1
BakoLight LED, flashing/steady light, one-sided red, without bracket	111241-3

Accessories and Spare parts

Order number

Pin	010393
Key	070090-3
Bracket for mounting the MonoLight and BakoLight	070877

Operating time with a battery pack

With battery Premium 800	one-sided steady light 250 hrs
	flashing light 750 hrs
	two-sided steady light 300 hrs
	flashing light 900 hrs
With battery Konstant 25	one-sided steady light 500 hrs
	flashing light 1500 hrs
	two-sided steady light 1000 hrs
	flashing light 3000 hrs



Packaging Unit
10 pcs in one carton / 200 pcs on one pallet
also available in other quantities



Further information
NIS-00741
Entry on nissen-germany.com

Verification number:
V4-01-2004 V4-02-2004 V4-47-2004