


# Konstant-Norm LED

- Fits all beacon systems when using the appropriate adapter (42 mm Ø, 40 x 40 mm)
- Battery will be separately placed in base plate
- Automatic solar switch



	<b>Light colour</b> amber		<b>Eff. light intensity</b> one-sided 30 cd / two-sided 16 cd		<b>Blink-/flash rate</b> 60 fl./min.		<b>Light source</b> 1 resp. 2 LED
	<b>Dimensions (LxWxH)</b> 207 x 88 x 270 mm		<b>Weight</b> 0,6 kg				



Locking bolt



Battery compartment

## Konstant-Norm LED

	Order number
Konstant-Norm LED, flashing/steady light, one-sided amber	111221-1
Konstant-Norm LED, flashing/steady light, two-sided amber	111222-1

## Accessories and Spare parts

	Order number
Cable with cold-device socket	052011-1
Locking bolt	010413-2
Pulser LED, two-sided amber	355522-11
Pulser LED, one-sided amber	355521-11

## Operating time with a battery pack

With battery Konstant 60	steady light 1050 hrs / flashing light 3000 hrs
With battery Konstant 111	steady light 1550 hrs / flashing light 4600 hrs



**Packaging Unit**  
15 pcs in one carton / 300 pcs on one pallet  
also available in other quantities



**Further information**  
NIS-00077  
Entry on nissen-germany.com

**Verification number:**  
V4-120-2003 V4-121-2003