


MonoLight LED

- High-quality LEDs with nearly unlimited life time
- Only one battery needed
- Lamp head adjustable, with reflective rim
- Automatic solar switch
- Optional with firmly mounted bracket for attachment to vertical tubes



Light colour
amber resp. red



Eff. light intensity
two-sided 15 cd /
omnidirectional 3 cd



Blink-/flash rate
60 - 70 fl./min.



Light source
1 bzw. 2 LED



Dimensions (LxWxH)
without bracket
185 x 120 x 340 mm



Weight
0.5 kg without bracket
0.6 kg with bracket




MonoLight omni-directional



MonoLight with bracket



NiKo key



Changing battery

MonoLight LED

Order number

MonoLight LED, flashing/steady light, two-sided amber, with bracket	111602-51
MonoLight LED, flashing/steady light, two-sided red, with bracket	111602-53
MonoLight LED, flashing/steady light, two-sided amber, without bracket	111602-1
MonoLight LED, flashing/steady light, two-sided red, without bracket	111602-3
MonoLight LED, flashing/steady light, omni-directional amber, without bracket	111605-1

Accessories and Spare parts

Order number

Bracket for mounting the MonoLight / SignLite on traffic cones	292032-3
NiKo bracket for mounting the MonoLight on barriers	365519
NiKo key	070090-1
Bracket for mounting the MonoLight and BakoLight	070877

Operating time with a battery pack

With battery Premium 800	steady light 300 hrs flashing light 1200 hrs
With battery Konstant 45	steady light 1400 hrs flashing light 5500 hrs



Packaging Unit
20 pcs in one carton / 400 pcs on one pallet
also available in other quantities



Further information
NIS-00216
Entry on nissen-germany.com