nissen ™

Euro-Nitra LED

- Easy attachment to barriers or tubes with the firmly mounted bracket
- Easy battery replacement without removing the lamp
- Automatic solar switch
- Useful loop for carrying or rapid attachment

190 mm

Lamp class
L6 L7
according to EN12352

European Norm
EN 12352
European Norm

BASt approved
BASt
BASt approved

BASt approved
WL1 WL2
according to "TL-Warnleuchten"

Light colour amber or red	**Eff. light intensity** amber one-sided 24 cd / two-sided 18 cd	**Eff. light intensity** red one-sided 20 cd / two-sided 20 cd	**Blink-/flash rate** 60 fl./min.
Light source 1 resp. 2 LED	**Dimensions (LxWxH)** 195 x 90 x 350 mm	**Weight** 0.7 kg	

Euro-Nitra LED	Order number
Euro-Nitra LED, flashing/steady light, one-sided amber, with bracket	112127-51
Euro-Nitra LED, flashing/steady light, one-sided red, with bracket	112127-53
Euro-Nitra LED, flashing/steady light, two-sided amber, with bracket	112128-51
Euro-Nitra-LED, flashing/steady light, two-sided red, with bracket	112128-53

Accessories and Spare parts	Order number
Pulser LED, two-sided red	358058-23
Pulser LED, two-sided amber	358058-21
Pulser LED, one-sided red	358057-23
Pulser LED, one-sided amber	358057-21
NiKo key	070090-1

Operating time with a battery pack

With battery Premium 800	steady light 250 hrs
	flashing light 750 hrs
With battery Konstant 45	steady light 1500 hrs
	flashing light 4500 hrs

With bracket

NiKo key

Changing battery

Further information
NIS-00079
Entry on nissen-germany.com

Verification number:
V4-120-2004 V4-117-2004 V4-80-2004

Subject to technical modifications. Pictures can differ from the original product. Version 03/2025

export@nissen-germany.com