

QuickFlash LED

- Only 1 LED, therefore low current consumption and long operating times
- Space saving storage due to stackability with locking aid
- Easy handling through the optimum positioning of carrying handles
- Low height in folded position due to integrated beacon in the base plate
- Lamp chain of any length and any amount of lamps possible
- Basic steady light for increased visibility at darkness
- Maintenance-free and robust folding hinge
- Synchronization by infrared diodes
- Automatic day/night adaptation
- Equipable with foil type RA2
- Mignon cells operation
(6 pieces per lamp)



	Light colour yellow		Eff. light intensity day 500 cd		Eff. light intensity night 250 cd		Blink-/flash rate 60 fl./min.
	Dimensions (HxWxD) 610 x 285 x 645 mm (lifted)		Dimensions (HxWxD) 72 x 285 x 645 mm (lowered)		Weight 5,5 kg		

QuickFlash LED

Order number

QuickFlash LED 630, housing colour yellow, lence one-sided amber, foil RA2, one-sided, red/white, with base plate	129103-002-100
QuickFlash LED 630, housing colour yellow, lence one-sided amber, foil RA2, two-sided, red/white, with base plate	129103-002-200

Accessories and Spare parts

Order number

Mignon cell (AA), alkaline manganese, 1,5V	155010
--	--------

Operating time with a battery pack

with mignon cell (AA), alkaline manganese, 1,5V	up to 150 h
---	-------------



Stackable so as to save space (side view)



Recessed grip

