

# QuickFlash LED

- Only 1 LED, therefore low current consumption and long operating times
- Space saving storage due to stackability with locking aid
- Easy handling through the optimum positioning of carrying handles
- Low height in folded position due to integrated beacon in the base plate
- Lamp chain of any length and any amount of lamps possible
- Basic steady light for increased visibility at darkness
- Maintenance-free and robust folding hinge
- Synchronization by infrared diodes
- Automatic day/night adaptation
- Equipable with foil type RA2
- Mignon cells operation  
(6 pieces per lamp)



	<b>Light colour</b> yellow		<b>Eff. light intensity day</b> 500 cd		<b>Eff. light intensity night</b> 250 cd		<b>Blink-/flash rate</b> 60 fl./min.
	<b>Dimensions (HxWxD)</b> 610 x 285 x 645 mm (lifted)		<b>Dimensions (HxWxD)</b> 72 x 285 x 645 mm (lowered)		<b>Weight</b> 5.5 kg		

## QuickFlash LED

## Order number

QuickFlash LED 630, housing colour yellow, lence one-sided amber, foil RA2, one-sided, red/white, with base plate	129103-002-100
QuickFlash LED 630, housing colour yellow, lence one-sided amber, foil RA2, two-sided, red/white, with base plate	129103-002-200

## Accessories and Spare parts

## Order number

Mignon cell (AA), alkaline manganese, 1,5V	155010
--	--------

## Operating time with a battery pack

with mignon cell (AA), alkaline manganese, 1,5V	up to 150 h
---	-------------



Stackable so as to save space (side view)



Stackable so as to save space (front view)



Recessed grip



Further information  
NIS-02154  
Entry on nissen-germany.com

Verification number:  
V3-01/2018

