


VarioSign LED Trailer

PREMIUM



CHASSIS AND BODY

- Chassis and body of hot-galvanized steel
- Hot-galvanized, height-adjustable drawbar with holding brake
- DIN towing eye and spherical head coupling changeable
- Loading area of 15 mm 7 layered laminated plywood sheets with sealed edges
- Side panels of 15 mm 7 layered laminated plywood covered with aluminium sheet profil at the top
- Loading area (1600 x 530 x 300 mm)
- Height-adjustable support wheel an 4 fully adjustable support legs
- Battery box of acid-proof plastic (1660 x 450 x 320 mm)
- Plastic fenders
- Handle for one-handed opening/closing of battery box

ADVANCE WARNING BOARD

- 2 LED advance warning lamps tested according to TL warning lamps WL 7
- 2 LED variable message signs with an automatic and manual brightness adjustment for the static and dynamic representation of texts, symbols and road signs

Upper LED variable traffic sign

Housing size:	1390 x 1390 mm
LED display surface:	1260 x 1260 mm
Pixels:	63 x 63
Grid dimension:	20 mm
LED/m ² :	2500

Lower variable traffic sign

Housing size:	1810 x 1810 mm
LED display surface:	1680 x 1680 mm
Pixels:	84 x 84
Grid dimension:	20 mm
LED/m ² :	2500

- Separately programmable text line
- Libraries on a separate memory module
- Motorized lifting and lowering of the top board with mechanical emergency adjustment and freely accessible emergency-off switch
- Electromotive locking in lowered state
- Combined manual radio-cable remote control for operating all functions via touchscreen and one-touch keys
- Free programming software

ELECTRICAL SYSTEM

- Rechargeable battery, 24 V with up to 50 hours daytime operation (further energy packages on request)
- Trailer lighting optionally 12 V and/or 24 V
- Feed socket 230 V
- Battery guard for protection of electronics
- Battery charger

ACCESSORIES AND OPTIONS

- Central crank supports
- Control and monitoring system
- Operating hours counter
- Interface package
- Spare wheel
- Traffic cone holder



Technical data

Total weight	A1: 1000 - 1300 kg, A2: 1300 - 1500 kg
Empty weight depending on model	A1: 810 kg, A2: 940 kg
Total length	A1: 3770 - 4500 mm, A2: 4800 - 5300 mm
Total width	2200 mm
Track width	2000 mm
Max. load capacity	A1: 190 - 490 kg, A2: 220 - 420 kg
Loading area (LxW)	A1: 1360 x 1620 mm, A2: 1870 x 1620 mm
Height lifted	3930 mm
Height lowered	2460 mm

VarioSign LED Trailer PREMIUM

Order number

Advance Warning Trailer VarioSign ADVANCED with LED variable message signs (A1) total weight 1300 - 1500 kg, with parking brake	129265-025
Advance Warning Trailer VarioSign ADVANCED with LED variable message signs (A2) total weight 1300 - 1500 kg, with parking brake	129265-026



Further information
NIS-01788
Entry on nissen-germany.com