

# MonoLight LED WL8

- High-quality LEDs with nearly unlimited life time
- Only one battery needed
- Optional with firmly mounted bracket for attachment to vertical tubes
- Automatic solar switch
- For securing areas such as pavements, bicycle paths and pedestrian areas etc.



**Light colour**  
amber



**Eff. light intensity**  
4 cd



**Blink-/flash rate**  
60 - 70 fl./min.



**Light source**  
4 LED



**Dimensions (LxWxH)**  
130 x 110 x 280 mm



**Weight**  
0.5 kg without bracket  
0.6 kg with bracket

## MonoLight LED WL8

### Order number

MonoLight LED WL8, flashing/steady light, omni-directional horizontal, amber, with bracket	111606-51
MonoLight LED WL8, flashing/steady light, omni-directional horizontal, amber, without bracket	111606-1

## Accessories and Spare parts

### Order number

Bracket for mounting the MonoLight and BakoLight	070877
NiKo key	070090-1
NiKo bracket for mounting the MonoLight on barriers	365519
Bracket for mounting the MonoLight / SignLite on traffic cones	292032-3

## Operating time with a battery pack

With battery Premium 800	steady light 210 hrs flashing light 700 hrs
With battery Konstant 45	steady light 820 hrs flashing light 2450 hrs



MonoLight with bracket



Changing battery



NiKo key



**Packaging Unit**  
15 pcs in one carton / 360 pcs on one pallet  
also available in other quantities



**Further information**  
NIS-01914  
Entry on nissen-germany.com

**Verification number:**  
V3-003-2016