

MonoLight LED WL8

- High-quality LEDs with nearly unlimited life time
- Only one battery needed
- Optional with firmly mounted bracket for attachment to vertical tubes
- Automatic solar switch
- For securing areas such as pavements, bicycle paths and pedestrian areas etc.



Light colour
amber



Eff. light intensity
4 cd



Blink-/flash rate
60 - 70 fl./min.



Light source
4 LED



Dimensions (LxWxH)
130 x 110 x 280 mm



Weight
0.5 kg without bracket
0.6 kg with bracket

MonoLight LED WL8

Order number

MonoLight LED WL8, flashing/steady light, omni-directional horizontal, amber, with bracket	111606-51
MonoLight LED WL8, flashing/steady light, omni-directional horizontal, amber, without bracket	111606-1

Accessories and Spare parts

Order number

Bracket for mounting the MonoLight / SignLite on traffic cones	292032-3
NiKo bracket for mounting the MonoLight on barriers	365519
NiKo key	070090-1
Bracket for mounting the MonoLight and BakoLight	070877

Operating time with a battery pack

With battery Premium 800	steady light 210 hrs flashing light 700 hrs
With battery Konstant 45	steady light 820 hrs flashing light 2450 hrs



MonoLight with bracket



Changing battery



NiKo key



Packaging Unit
15 pcs in one carton / 360 pcs on one pallet
also available in other quantities



Further information
NIS-01914
Entry on nissen-germany.com

Verification number:
V3-003-2016