

Sequential Direction Light Set LED

- Consisting of 1 master lamp and up to 9 slave lamps
- Robust cable plug connection between the single lamps
- With solar switch
- Fits all beacon systems when using the appropriate adapter (42 mm Ø, 40 x 40 mm)
- Adjustable as guide light, sequential direction light, flashing light, steady light



Light colour yellow	Eff. light intensity 1500 cd	Av. power consumpt. day 1.3 A	Operating voltage 12/24 V
Blink-/flash rate 60 fl./Min.	Light source 1 LED	Dimensions 207 x 88 x 270 mm (single lamp)	Weight 0.6 kg (single lamp)

Sequential Direction Light Set LED

Order number

10-fold Sequential Direction Light Set LED Type 640, 230/12V without beacons 120911-1

Accessories and Spare parts

Order number

Battery central feed with connector housing 400210-05
 Cascade lamp 200 LED, yellow without beacons 122216-01
 Box for rechargeable batteries 12V up to 230 Ah, lockable 190230-1
 Remote control for Sequential Direction Light Set type 640 329301-01
 Charger 230/12V, 17A 220909-2

Operating time with a battery pack

With rechargeable battery 12V, 100 Ah 10-fold system - 80 hrs
 With rechargeable battery 12V, 180 Ah 10-fold system - 140 hrs
 With rechargeable battery 12V, 230 Ah 10-fold system - 180 hrs




Fixation at a Standard Beacon



Box for rechargeable battery, lockable



Remote control for Sequential Direction Light Set



Battery central feed with connector housing



Further information
 NIS-01983
 Entry on nissen-germany.com

