

# Twofold Warning System Zyklus 340 LED L9H

- Energy-efficient LED technology
- Automatic day/night adaptation, switchable to solar switch
- Consisting of one master lamp and one slave lamp, cable length between the lamps 5 m
- Master lamp with 5 m connecting cable with battery clips
- Approved according to EMC directive
- Bracket for tubes up to 82 mm



<b>Light colour</b> yellow	<b>Eff. light intensity day</b> 20000 cd	<b>Av. power consumpt. day</b> 0,5 A	<b>Av. power consumpt. day</b> 0,5 A
<b>Operating voltage</b> 12/24V	<b>Blink-/flash rate</b> 60 fl./min.	<b>Light source</b> 1 LED	<b>Dimensions</b> Ø 350 mm / Höhe: 96 mm
<b>Weight</b> Ø 350 mm / height: 96 mm	<b>Weight</b> 2.5 kg/set		

## Twofold Warning System Zyklus 340 LED L9H

### Order number

Twofold Warning Light System Zyklus LED L9H (NiBus) 12/24 V, with bracket, with 5 m connecting cable with battery clips on master lamp

122322-001

## Accessories and Spare parts

### Order number

Box for rechargeable batteries 12 V up to 230 Ah, lockable

190230-1

## Operating time with a battery pack

With rechargeable battery 12V, 100 Ah

250 hrs

With rechargeable battery 12V, 180 Ah

450 hrs



Twofold Warning System Zyklus with bracket



Box for rechargeable batteries



Further information  
NIS-01984  
Entry on [nissen-germany.com](http://nissen-germany.com)