

Twofold Warning System Multi-Light 340 LED L9H

- Engery-efficient LED technology
- Automatic day/night adaptation, switchable to solar switch
- Consisting of one master lamp and one slave lamp, cable length between the lamps 5 m
- Master lamp with 5 m connecting cable with battery clips
- Bracket for tubes up to 82 mm



Light colour yellow	Eff. light intensity day 20000 cd	Av. power consumpt. day 0,8 A	Av. power consumpt. day 0.8 A
Operating voltage 12/24V	Blink-/flash rate 60 fl./min.	Light source 4 LED	Weight 5.4 kg/set

Twofold Warning System Multi-Light 340 LED L9H

Order number

Twofold Warning Light System Multi-Light 340 LED L9H 690/1 NiBus, 12/24V, with bracket, with 5 m connecting cable with battery clips on master lamp	122312-1
Twofold Warning Light System Zyklus LED L9H (NiBus) 12/24V, with bracket, with 5 m connecting cable with battery clips on master lamp	122322-001
Twofold Warning Light System Zyklus LED Flash L9M (NiBus) 12/24V, with bracket, with 5 m connecting cable with battery clips on master lamp	122322-021


Accessories and Spare parts

Order number

Box for rechargeable batteries 12V up to 230 Ah, lockable	190230-1
---	----------

Operating time with a battery pack

With rechargeable battery 12V, 100 Ah	150 hrs
With rechargeable battery 12V, 180 Ah	350 hrs



Twofold Warning S. Multi-Light 340 LED L9H



Twofold Warning System with bracket



Box for rechargeable batteries



Further information
NIS-00546
Entry on nissen-germany.com

Verification number:
V4-59-2011

