

Warning Trailer

B2



CHASSIS AND BODY

- Chassis and body of galvanized steel
- Galvanized, height-adjustable drawbar (Al-Ko), with overrun brake, holding brake and parallel adjustment
- DIN towing eye with a changeable spherical head coupling
- Loading area of 15 mm 7 layered laminated plywood sheets with sealed edges
- Side panels of 15 mm 7 layered laminated plywood covered with aluminium sheet profil at the top
- Height-adjustable semi-automatic support wheel
- Robust plastic fenders
- Battery box integrated into the side panel design incl. cover of aluminium chequered plate (1000 x 400 x 300 mm)
- Braked rubber spring axle
- 4 lashing points (straps) with 500 daN
- 2 fully adjustable support legs

WARNING BOARD

- Warning board in compliance with RSA 21 and ZTV-SA, 2500 x 1700 mm
- Chevron patterned plates and directional arrow with microprismatic retro-reflective foil, type RA2
- Light arrow system with two LED warning lamps (WL5) and 15 separately monitored LED warning lamps (WL6)
- Directional arrow with motor revolution, mechanical emergency and automatic light arrow adjustment
- Manual lifting and lowering of the top board
- Manual cable or radio control for operating all functions via one-touch keys

ELECTRICAL SYSTEM

- Rechargeable battery 12 V, up to 55 hours daytime operation (further energy packages on request)
- Trailer lighting optionally 12 V and/or 24 V
- Feed socket 230 V
- Battery charger
- Battery disconnecter

ACCESSORIES AND OPTIONS

- Battery guard for protection of electronics
- Cargo securing set
- Central crank supports
- Control and monitoring system
- Motorized lifting and lowering of the top board
- Traffic cone holder



Sign 615

Technical data

Total weight	300 mm
Empty weight depending on model	750 - 1000 kg
Total length	4200 mm
Total width	1700 mm
Track width	1400 mm
Track width	400 - 450 kg
Max. load capacity	350 - 550 kg
Loading area (LxW)	1760 x 1000 mm

Warning Trailer Type B2

Order number

Warning Trailer Type B 2, without light warning system

129700-002



Further information
NIS-00587
Entry on nissen-germany.com